



HANSA

Installation and maintenance guide




4-13



14-22



23



24-31



32



HANSA Connect App
 HANSA Connect App


ltansa.com/ltansa-app

Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc., registered in the U.S. and other countries.




Google Play and the Google Play logo are trademarks of Google Inc.

The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Hansa Armaturen GmbH is under license. Other trademarks and trade names are those of their respective owners.










Lithium 2CR5 6 V
 I (ISO 3822)
 EN 15091
 100 - 1000 kPa

max. +70°C
 IP 55

**6441 2219** mpi.hansa.com/64412219


0615 2219
0615 2219 33
6416 2219

mpi.hansa.com/06152219**5716 2219** mpi.hansa.com/57162219**6440 2219** mpi.hansa.com/64402219






Lithium 2CR5 6 V
 I (ISO 3822)
 EN 15091
 100 - 1000 kPa

max. +70°C
 IP 55





6443 2219 ❄️






mpi.hansa.com/64432219

6541 2219 ❄️ 0.08 l/s



mpi.hansa.com/65412219

6491 2219 ❄️




mpi.hansa.com/64912219





Lithium 2CR5 6 V
 I (ISO 3822)
 EN 15091
 100 - 1000 kPa

max. +70°C
 IP 55





5716 2279





mpi.hansa.com/57162279

6444 2229





mpi.hansa.com/64442229

6444 2219



mpi.hansa.com/64442219

5749 2219




mpi.hansa.com/57492219




Lithium 2CR5 6 V
 I (ISO 3822)
 EN 15091
 100 - 1000 kPa

max. +70°C
 IP 55





5193 2201 ❄️





mpi.hansa.com/57162279

5179 2201 ❄️



mpi.hansa.com/64442229

5194 2201 ❄️













mpi.hansa.com/64442219



9 / 12 V
 I (ISO 3822)
 EN 15091
 100 - 1000 kPa


max. +70°C
 IP 55

**5712 2209** ❄️mpi.hansa.com/57122209**6443 2009** ❄️mpi.hansa.com/64432009**6442 1109** ❄️ 100 - 500 kPampi.hansa.com/64421109**6541 2079** ❄️mpi.hansa.com/65412079




9 / 12 V
 I (ISO 3822)
 EN 15091
 100 - 1000 kPa

max. +70°C
 IP 55





5193 2211





mpi.hansa.com/51932211

5179 2221



mpi.hansa.com/51792221

5194 2211










mpi.hansa.com/51942211



230 / 9 V
 I (ISO 3822)
 EN 15091
 100 - 1000 kPa


max. +70°C
 IP 55 / transformer IP 20

**6541 2009** mpi.hansa.com/65412009**6491 2019** mpi.hansa.com/64912019**6441 2009** mpi.hansa.com/64412009**5712 2279** mpi.hansa.com/57122279





230 / 9 V
 I (ISO 3822)
 EN 15091
 100 - 1000 kPa

max. +70°C
 IP 55 / transformer IP 20




6443 2029 ❄️




mpi.hansa.com/64432029

6442 1129 ❄️





mpi.hansa.com/64421129

0614 2209 ❄️



mpi.hansa.com/06142209

5748 2209 ❄️




mpi.hansa.com/57482209






230 / 12 V
I (ISO 3822)
EN 15091
100 - 1000 kPa

max. +70°C
IP 55






6443 2019



mpi.hansa.com/64432019

6442 1119





mpi.hansa.com/64421119




- GB** Power supply requirement: Power supply output must be short circuit protected
- CZ** Požadavky týkající se napájecího zdroje: Výstup napájecího zdroje musí být chráněn proti zkratu
- DE** Stromversorgungs-voraussetzungen: Stromversorgungsspannung muss kurzschlussgeschützt sein.
- DK** Krav til strømforsyning: Strømforsyningsudgang skal være kortslutningsbeskyttet
- EE** Nõuded vooluallikale: Vooluallika väljund peab olema kaitstud lühise eest
- ES** Requisitos del suministro eléctrico: el suministro eléctrico debe estar protegido contra cortocircuitos
- FI** Vaatimukset virtalähteelle: Virtalähteen ulostulon tulee olla oikosulkusuojattu
- FR** Unité d'alimentation électrique: La sortie de l'unité d'alimentation oit être protégée contre le court-circuit
- IT** Requisiti dell'alimentazione: L'uscita deve essere protetta da cortocircuiti
- LT** Reikalavimai maitinimo šaltiniui: turi būti apsauga nuo trumpo jungimo
- NL** Prasības attiecībā uz barošanas ierīci: ierīces izvadām jābūt aizsargātām pret īsslēgumiem
- NO** Vereisten voor de voeding: De uitgang van de voeding moet beschermd zijn tegen kortsluitingen
- NO** Krav til strømforsyning: Strømforsyningspenning må være kortslutningssikret
- PL** Wymagania w stosunku do zasilacza: Zasilacz musi być wyposażony w zabezpieczenie przeciwzwarciowe
- RO** Pentru alimentarea cu putere: borna de putere trebuie să fie protejată la scurtcircuit
- RU** Требования к источнику тока: Выход источника тока защищен от короткого замыкания
- SE** Krav på matningsdön: Utspänningen skall vara kortslutningssäker
- SK** Požiadavka na napájanie: Výstup napájania musí byť chránený voči skratu.
- UA** Вимоги до джерела струму: Вихід джерела струму захищений від короткого замикання.
- PT** Requisitos de alimentação eléctrica: a alimentação eléctrica deve estar protegida contra curto-circuito.
- GR** Προϋποθέσεις για αδιάλειπτη παροχή ρεύματος: Τάση εξόδου ασφαλισμένη έναντι βραχυκυκλώματος
- SI** Zahteva za napajanje: Izhod za napajanje mora biti zaščiten s kratkim stikom
- HU** Áramellátás: A tápegység kimeneténél fontos az érintésvédelmet biztosítani.


Hansa 6499 0100








Oras 199275




1.....5












1 A















1 B





1 C










1 2

max.
1600 kPa

2 A



2 B





19


①②③④




max.
1600 kPa




2C




1



3





2






3 A





3 B



6449 0900















3 C



6499 0100

3 D










AUTOMATIC

2 s ± 1 s

max. 2 min

Bluetooth®







HANSA Connect App


Download on the
App Store

GET IT ON
Google Play


hansa.com/hansa-app








Lithium 2CR5 6V

















2.5







① ②




























Oras Group is a powerful European provider of sanitary fittings: the market leader in the Nordics and a leading company in Continental Europe. The company's mission is to make the use of water easy and sustainable and its vision is to become the European leader of advanced sanitary fittings. Oras Group has two strong brands: Oras and Hansa.

The Group's head office is located in Rauma, Finland, and the Group has three manufacturing sites: Kralovice (Czech Republic), Olesno (Poland) and Rauma (Finland). Oras Group employs approximately 1,200 people in twenty countries. Oras Group is owned by Oras Invest, a family company and an industrial owner.

HANSA Armaturen GmbH
P. O. BOX 81 02 40
D-70519 Stuttgart
Sigmaringer Strasse 107
D-70567 Stuttgart
Tel.: +49 711 16 14 0
Fax: +49 711 16 14 368
info@hansa.de
www.hansa.com



943421D-08-23