


## 50-ISO4-R20-RO: Henco RIXC Ø20x2 ISO 6mm Red 50m



### Commercial information

The multilayer pipes come with a round or eccentric thermal insulating material. This material is made from extruded PE foam with a closed cell. The PE foam has a sturdy outer layer made from PE with a red or blue meshed vapour tight structure. This protects the foam against damage, so that the insulating properties of the product are not lost even during rough building work.

#### Basic unit dimensions

Height	32 mm
Length	1,000 mm
Width	32 mm
Net weight	0.178 kg

#### Certificates

ATG, QB (CSTBat), DVGW Wasser, KOMO, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, ETA, SITAC, Bureau Veritas, SINTEF, WRAS, AFNOR, STF, ACS, Aenor, WQA, EMI

#### Applications

Potable water, Heating, Cooling, Compressed air, Demi Water, Sanitary



#### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

Material inner layer	Plastic (expired)	Number of layers	5
Quality class inner layer	PE-Xc	Outer pipe diameter	20 Millimetre
Material intermediate layer	Aluminium	Wall thickness	2 Millimetre
Material outer layer	Plastic (expired)	Medium temperature (continuous)	- Degrees celsius 10 7 0
Quality class outer layer	PE-Xc	Max. medium temperature (momentarily)	95 Degrees celsius
Glass-fibre reinforced	✘	Max. operating pressure at 20 °C	10 Bar
Diffusion-proof	✓	Max. operating pressure at max. medium temperature	10 Bar
Nominal diameter	DN 16	Wall roughness	0.00 Millimetre 7
System specific	✓	Expansion coefficient	0.02 Millimetre per metre Kelvin 5
Flexible	✓	Min. bending radius	60 Millimetre
Suitable for surface mounting	✓	Min. bending radius without tools	60 Millimetre
Pipe colour	Red	Outer diameter mantle pipe	0 Millimetre
With mantle pipe	✘	Thickness of thermal insulation	6 Millimetre
Gastec QA	✘	Lambda value	0.43 Watt per metre Kelvin
KIWA certified	✘	Outer diameter thermal insulation	32 Millimetre
With heating cable	✘	Outer width rectangular insulation	0 Millimetre
KOMO certified	✓	Outer height rectangular insulation	0 Millimetre
With thermal insulation	✓	Water content	0.20 Litre per metre 1
Shape of insulation	Round		
Colour of thermal insulation	Red		
DVGW quality mark	✓		
SVGW certified	✘		
Capped	✘		
UV resistant	✘		
Halogen free	✓		
Hook-and-loop fastening	✘		
Certified according to SVGW for water	✘		
Certified according to SVGW for gas	✘		
DIN-CERTCO certificate	✘		
With approval for TÜV	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✓		
Compliant with NF 545	✓		
KIWA certified	✘		
Gastec QA mark	✘		
KOMO certified	✓		
Type approval according to BBR/EKS	✘		

## Related products

Product code	GTIN	Description	Image
IM1426PRESS	05414764035621	Henco Guillotine cutter 14-26mm	
KS20M	05414764035621	Henco Kalispeed (max. 500 rpm, clockwise) Ø20	

Product code	GTIN	Description
KS-K	05414764035621	Henco Clickhandle for KS (Kalispeed)
TESTPLUG20	05414764035621	Henco Test cap for pipe Ø20
BI-2016	05414764035621	Henco Internal Bending spring 20x2 l=50
BDR33M	05414764035621	Henco Mounting/repair tape for insulation red 33m x 50mm

Image

