

UFH-060504-MD: 4-groups Manifold brass,adjustable,with flow meters



Commercial information

Brass manifold for both housing and utility buildings. It is compact in construction and allows smooth installation. This manifold is equipped with flowmeters and fine regulating valves for each circuit. Outlets are connected to eurocone3/4".

Basic unit dimensions

Height	320 mm
Length	260 mm
Width	100 mm
Net weight	2.450 kg

Certificates

Applications

Heating, Cooling, Underfloor Heating

Solutions

Underfloor heating, Building installations, Industry, Utility

Technical characteristics

Connection type primary side	2-pipe	Outer pipe diameter primary connection	32 Millimetre
Suitable for cooling	✓	Medium temperature (continuous)	0 80 Degrees celsius
Material	Brass	Max. operating pressure	6 Bar
Position primary connection	Left/right	Max. number of expansion groups	0
Primary connection	External thread cylindrical BSPP-G (ISO 228-1)	Number of groups secondary	4
Nominal diameter primary connection	1 inch (25)	Outer pipe diameter secondary	12 20 Millimetre
With valves on primary connection	✗	Flow-through capacity	0 6 Litre per hour
With mixing valve	✗	Min. pressure difference secondary flow/return	0 Kilo Pascal
Expandable	✗	Width	100 Millimetre
Multi-zone manifold	✗	Height	320 Millimetre
With temperature limit	✗	Depth	260 Millimetre
With non-return valve	✗		
With circulation pump	✗		
Article compression class	PN 6		
With controller	✗		
Hydraulic balance control	None		
Volume flow measurement	Analogue		
With thermometer	✗		
Temperature measurement supply	None		
Temperature measurement return	None		
With de-aeration	✗		
With pressure gauge	✗		
Secondary connection	Euroconus standardless		
Nominal diameter secondary connection	3/4 inch (20)		
Closable groups	✓		
With flow-through indicator	✓		
With thermal actuator	✗		
With wall-mounting bracket	✓		
With casing	✗		

Related products

Product code	GTIN	Description
UFH-CAB-I455	05414764139909	Henco Recessed manifold cabinet RAL9003 internal width 455MM
UFH-CAB-O615	05414764139909	Henco Surface mount cabinet RAL9003 internal width 615MM
UFH-CAB-O615Z	05414764139909	Henco Surface mount cabinet backless RAL9003 internal width 615MM
UFH-M-R	05414764139909	Henco Regulating Valve RP630 3/8" UFH-0605..-MR

Image



Product code	GTIN	Description	Image
UFH-BTM0606-M	05414764139909	Henco 1 F ball valve with 1 F swivel nut,washer and thermometer	
UFH-PGKTA	05414764139909	Henco Pump unit with consistent temperature control	
UFH-B0606-M	05414764139909	Henco 1 f ball valve with 1 f swivel nut and washer	
UFH-ESK060303-M	05414764139909	Henco 1 F end cap with nut,washer,ball valve and air vent 3/8	
UFH-TM050-M	05414764139909	Henco Thermometer for return with EK connections	
UFH-BS05-M	05414764139909	Henco End cap with washer 3/4	